



F 18 Standalone Fingerprint Reader Controller

Modern standalone fingerprint controller with color display



Biometric Performance:

Reliable, durable and highly accurate ZK fingerprint sensor with latest fingerprint matching algorithm which provides less than 1.5 second user recognition.



Communication:

Weigand output for connecting to access control panel and Ethernet port for fast and reliable commu nication with the computer



Easy Operation and Management:

Works without computer. Complete setup and pro gramming can be done via keypads and embedded firmware. Audio-Visual Indication for acceptance and rejection of valid/invalid fingerprints, cards and passwords.



Options:

Internal Proximity Card or Mifare Card reader allows dual factor authentication for access control.



Full Access Control Built In:

Relay Outputs for electric lock and alarm. Inputs fordoor status sensor and request to exit hardware. Supports multipletimezones and personnel groups for programming valid entry zones.



Capacity:


Can store up to 3,000 templates and 30,000 transac tions. The data can be backed up to a USB flash drive and can also be transferred to another reader in the absence of computer connectivity.



For Software Developers:

Free SDK and development tools are available for developers/partners who wish to integrate F18 with any application which requires verifying people. Cus tom development is also available for OEM partners upon request.

Standalone Installation



Specifications

Capacity

Fingerprint: 3,000 templates Transactions: 30,000

Display 3.5in TFT LCD Color Display

Communication

Ethernet, Weigand Input and Output, RS485, USB Host

Access Control Interface


3rd party electric lock, Door sensor, Exit button, Alarm, Door bell

Power 12V DC, 3A

Environment

Operating Temperature: 32° to 113° F (0° to 45° C) Operating Humidity: %20 to %80

Installation with Access Control Panel



Supported Options

ID Card, Mifare Card

Dimensions

Height: 7.20in (18.3cm) Length: 3.15in (8.0 cm) Width: 1.65in (4.2 cm) Weight: 0.90lbs (0.41kg)





AC Power Adapter



F-18ID with Proximity card reader F-18HID with HID card reader F-18M with Mifare card reader



Design and Specifications subject to change without notice

6 Kingsbridge Road, Suite 8 Fairfield, NJ 07004 2101 505 862 1+ sales@zkaccess.com zkaccess.com

What's in the Box



Andrew C. Bullingham Ē⊕ ۲



Installation Template

Network Cable

Back Plate







Screwdriver Screws

