

KR Series Wiegand Readers



KR100 E/M






KR101 E/M



KR300 E/M



KR200 E/M







KR202 E/M



KR201 E/M

Product Description

The KR Series is the main accessories line of external wiegand readers for all our access control devices. With an elegant and robust design, they are easy to connect and install, and offer the possibility to control one door from both sides. The LED lights indicate allowed or denied access. They have a proximity reading range of up to 10cm in the E series case and up to 5cm in the M series case. The fact that this series is waterproof, and the operating temperatures can range from -20° to +65°, it is the ideal solution for outdoor installation. Also they can be connected with our C3 controllers.

Features

- ✓ Easy to install
- 125KHz Proximity/13.56MHz Mifare Card Reader
- Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- 26/34bit Wiegand (default)
- Easy to install on Metal Door Frame or Mullion
- External LED Control
- External Buzzer Control
- Indoor / Outdoor Operation
- Solid Epoxy Injection
- Waterproof IP65
- **Reverse Polarity Protection**
- ✓ Elegant and robust design



KR Series Wiegand Readers



Specifications

| Model | KR100E/M | KR101E/M | KR102E/M | KR200E/M | KR201E/M | KR202E/M | KR300 |
|--|---|--|--|---|--|--|---|
| Read Range | KR100E Up to 10 CM KR100M Up to 5 CM | KR101E Up to 10 CM KR101M Up to 5 CM | KR2102E Up to 10 CM KR102M Up to 5 CM | KR200E Up to 10 CM KR200M Up to 5 CM | KR201E Up to 10 CM KR201M Up to 5 CM | KR202E Up to 10 CM KR202M Up to 5 CM | Up to10CM |
| Reading time (Card) | ≤ 300 ms | ≤300ms | ≤300ms | ≤300ms | ≤300ms | ≤300ms | ≤300ms |
| Power | DC 6-14V / Max.70mA | DC 6-14V / Max.70mA | DC 6-14V / Max.70mA | DC 6-14V / Max.70mA | DC 6-14V / Max.70mA | DC 6-14V / Max.70mA | DC 6-14V / Max.70mA |
| Input Port | 2ea (External LED Control, External Buzzer Control) | 2ea (External LED Control, External Buzzer Control) | 2ea (External LED Control, External Buzzer Control) | 2ea (External LED Control, External Buzzer Control) | 2ea (External LED Control, External Buzzer Control) | 2ea (External LED Control, External Buzzer Control) | 2ea (External LED Control, External Buzzer Control) |
| Output Card Format | 26bit Wiegand (E) 34bit Wiegand (M) | 26bit Wiegand (E) 34bit Wiegand (M) | 26bit Wiegand (E) 34bit Wiegand (M) | 26bit Wiegand (E) 34bit Wiegand (M) | 26bit Wiegand (E) 34bit Wiegand (M) | 26bit Wiegand (E) 34bit Wiegand (M) | 26bit Wiegand (E) 34bit Wiegand (M) |
| Output Pin Format | | | 8 bits | | | 8 bits | |
| LED indicator | 2 Color LED Indicators | 2 Color LED Indicators | 2 Color LED Indicators | 2 Color LED Indicators | 2 Color LED Indicators | 2 Color LED Indicators | 2 Color LED Indicators |
| LED malcator | (Red and Green) | (Red and Green) | (Red and Green) | (Red and Green) | (Red and Green) | (Red and Green) | (Red and Green) |
| Beeper | (Red and Green) yes | (Red and Green) | yes | (Red and Green) | yes | (Red and Green) | (Red and Green) |
| | | | | | | | |
| Beeper | yes | yes | yes | yes | yes | yes | yes |
| Beeper Operating temperature | yes "-20° to +65°C" 10% to 90% (relative humidity | yes "-20" to +65°C" 10% to 90% (relative humidity | yes "-20° to +65°C" 10% to 90% (relative humidity | yes "-20° to +65°C" 110% to 90% (relative humidity | yes "-20° to +65°C" 10% to 90% (relative humidity | yes "-20° to +65°C" 10% to 90% (relative humidity | yes "-10° to +70°C" 10% to 90% (relative humidity |
| Beeper Operating temperature Operating Humidity | yes "-20° to +65°C" 10% to 90% (relative humidity non-considered) | yes "-20° to +65°C" 10% to 90% (relative humidity non-considered) | yes "-20° to +65°C" 10% to 90% (relative humidity non-considered) | yes "-20" to +65"C" 110% to 90% (relative humidity non-considered) | yes "-20° to +65°C" 10% to 90% (relative humidity non-considered) | yes "-20" to +65°C" 10% to 90% (relative humidity non-considered) | yes "-10° to +70°C" 10% to 90% (relative humidity non-considered) |
| Beeper Operating temperature Operating Humidity Color | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black | yes "-20" to +65"C" 110% to 90% (relative humidity non-considered) Black | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black | yes "-20" to +65°C" 10% to 90% (relative humidity non-considered) Black | yes "-10" to +70"C" 10% to 90% (relative humidity non-considered) Black |
| Beeper Operating temperature Operating Humidity Color Material | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black ABS+PC with texture | yes "-20" to +65°C" 10% to 90% (relative humidity non-considered) Black ABS+PC with texture | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black ABS+PC with texture | yes "-20" to +65"C" 110% to 90% (relative humidity non-considered) Black ABS+PC with texture | yes "-20° to +65°C" 10% to 90% (relative humidity non-considered) Black ABS+PC with texture | yes "-20" to +65"C" 10% to 90% (relative humidity non-considered) Black ABS+PC with texture | yes "-10" to +70"C" 10% to 90% (relative humidity non-considered) Black ABS+PC with texture |

Connectivity diagram



ZKTeco Ind

ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town, Longgang District, Shenzhen China 518129 Tel: 86-755-8960 2345/46/47/48 E-mail: sales@zkteco.com www.zkteco.com

Global Offices:

USA: +1732-412-6007 EU: +34 916532891 Brazil: +55 31 2515-8326 Thailand: +66-027199154 Mexico: +52-55-52928418 South Africa: +27 12 259 1047 Egypt: +201110444134 Dubai: +974 1 6091 310 India: +91 8123536788 Indonesia: +62 21 2921 8949 Vietnam: +84-0169-5813007 Philippines: +63 9084118832 Russia: +8 915 178-46-81





