

ZK1515

All in One Biometric Smart Pos Terminal



Features

- Power-efficient Intel® Celeron J2.0 1900 GHz Quad-Core processor;
- Optional Intel® Core i3 and i5 processor;
- 15" Bezel-Free True-Flat PCAP touch screen;
- Multiple I/O interfaces for peripherals;
- Standard with 2G RAM and 32G SSD;
- Standard with 8C high-definition digital tube;
- Optional 3 tracks MSR, attached VFD & 12.1" customer display;
- Easy Installation and Durable;

Optional



Magnetic Stripe Card Reader



2nd LCD Display Screen



Barcode Scanner



Mifare/RFID



Thermal Printer



Cash Drawer



VFD Customer Display



Fingerprint

Specifications

Model Name	ZK1515
System	
Processor	Intel® Celeron J1900 Quad-Core processor (2.0 GHz)
System Memory	2GB Standard, DDR3L 1333MHz (Max.8GB)
Storage Device	32GB SSD Standard, 2.5*1" HDD & 2.5" SSD
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux
Audio	Realtek ALC662
Display and Touch	
Type	15" TFT LCD, LED Backlight
Resolution	768x1024
Touch Screen	Projected Capacitive Touch Screen
External I/O Ports	
VGA	1*DB15-
USB	5*USB 1 & 2.0*USB 3.0
Serial	1*RS232 (Max.4pcs)
LAN	1*RJ45
Audio	1*Line-out
Power	
Power Supply	Adaptor 12V DC 5A
Physical Environment	
Operating Temperature	0°C ~ 35°C at %80 - %20 Humidity
Storage Temperature	- 20°C ~ 55°C at %80 - %20 Humidity
Dimensions (WxHxD)	222*368*358 mm
Packing Dimensions	260*430*405 mm
Net Weight	5.5kg
Packing Weight	6.5kg
Certification	CE FCC
Color	Black
Options & Peripherals	
2nd Display	12.1" TFT LCD
Customer Display	20 Columns × 2 Lines
MSR	3 Tracks
Fingerprint	USB fingerprint reader (SLK20R)

